

TS07312017 Rev A

Solutions Architect of Technical Services



#### Copyright © 2017 Elo Touch Solutions, Inc. All Rights Reserved.

No part of this publication may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language or computer language, in any form or by any means, including, but not limited to, electronic, magnetic, optical, chemical, manual, or otherwise without prior written permission of Elo Touch Solutions, Inc.

#### Disclaimer

The information in this document is subject to change without notice. Elo Touch Solutions, Inc. and its affiliates (collectively "Elo") makes no representations or warranties with respect to the contents herein, and specifically disclaims any implied warranties of merchantability or fitness for a particular purpose. Elo reserves the right to revise this publication and to make changes from time to time in the content hereof without obligation of Elo to notify any person of such revisions or changes.

#### **Trademark Acknowledgments**

AccuTouch, CarrollTouch, Elo, Elo (logo), Elo Touch, Elo Touch Solutions, Elo TouchSystems, IntelliTouch, iTouch, SecureTouch, TouchTools and VuPoint are trademarks of Elo and its affiliates. Windows is a trademark of Microsoft Corporation.

# **Table of Contents**

Introduction	4
Tools Needed	5
Procedure	6

# **About This Manual**

This document guides the user through removing/replacing the RAM on the Elo i-Series with Windows AIO touchcomputer.

The intended audience of this document includes: IT engineers, system engineers, electrical engineers, and end-users.

If after reading through this guide, you still have questions or need help getting your system up and running, please contact an Elo Touch Solutions Technical Representative. <u>www.elotouch.com</u>

### **Tools Needed**

### Hardware needed:

### Hardware:

- Flat protective surface
- Elo i-Series with Windows AIO Touchcomputer
- Small Philipps Screwdriver
- Replacement or Additional RAM

### i-Series with Windows RAM Specifications:

- ESYxxi2: 2GB DDR3L SODIMM on 1 of 2 slot (Expandable to 8GB) NOTE: Maximum memory using 2 available slots; Replaceable up to 8GB maximum, SODIMM DDR3L-1600
- ESYxxi5: 4GB DDR4 SODIMM on 1 of 2 slot (Expandable to 16GB) NOTE: Maximum memory using 2 available slots; Replaceable up to 16GB maximum, SODIMM DDR4-2133

## Procedure

1. Place i-Series face down on a flat protective surface.



2. Using fingers pull up on the two tabs on the bottom of the back cover and push up and forward to remove the cover.



3. Remove two Philipps screws from metal plate and remove plate.





4. Add or replace RAM.



5. Reassemble i-series by following above procedure in reverse.

### Check out our website

# www.elotouch.com

Get the latest ...

- Product Information
- Specifications
- Upcoming events
- Press releases
- Software drivers

## **Getting in Touch with Us**

To find out more about the extensive range of Elo touch solutions, visit our website at www.elotouch.com, or simply call the office nearest you:

North America Elo Touch Solutions 1033 McCarthy Blvd Milpitas, CA 95035 Tel 800-ELO-TOUCH Tel + 1 408 597 8000 Fax +1 408 597 8050 customerservice@elotouch.com Europe Tel +32 (0) 16 70 45 00 Fax +32 (0)16 70 45 49 elosales@elotouch.com Asia-Pacific Tel +86 (21) 6106 7162 Fax +86 (21) 6485 3981 www.elotouch.com.cn Latin America Tel 786-923-0251 Fax 305-931-0124 www.elotouch.com